

KEY ADVANTAGES

- The safest paint stripper! Meets Canada's ECO logo & California rule 66
- Will not burn skin
- Removes multiple layers of paint in one application
- Will not raise the grain or fur the wood
- Contains NO Methylene Chloride, Caustics, Acids or MEK
- Hangs to vertical surfaces
- Stays wet longer allowing for the removal of lead based paints
- Will not harm glue or veneer
- Requires no neutralizing prior to recoating. Leaves surface PH Neutral

SAFETY PRECAUTIONS

- Avoid eye contact
- Never use near open flames, electrical or sparks
- Wear protective safety equipment, gloves, goggles and respirator if necessary
- Never use STRIP THIS!™ with any electrical equipment that can cause a spark or ignition. Always ventilate the area with fresh air.

850
**strip
this!**™

IMCO
TECHNOLOGIES INC.®

For over 20 years, IMCO® has taken a problem solving approach to product development, working closely with our customers to develop targeted engineered products that are ideally suited to specific applications.

www.imcotechnologies.com
1-888-818-4626

Distributed By:






INDUSTRIAL

- Flooring, walls, lead based paints



MARINE

- Won't harm fibreglass
- Strips, teak, steel, aluminum



RESIDENTIAL

- Removes oil or water based paints and stains, on wood floors, trim, furniture & sealers on concrete surfaces



AVIATION

- Will not harm structural integrity
- Helicopters and small planes



TRANSPORTATION

- Trains, box cars, ships, military equipment



COMMERCIAL

- Flooring, walls, schools, apartments, heritage buildings

Will remove latex, oil based enamels, epoxy, coal tar epoxy, urethanes, polyurethane, shellac, varnish, lacquers, elastomeric and clear coats from wood, metal brick, concrete, fibreglass and stone

Coverage: 100 square ft/gallon.

Spray Equipment: Use a quality airless spray gun with a 0.55 orifice and pressure between 40 to 60 psi. Keep compressor away from work area.



850 STRIP THIS!™ is a semi paste paint and varnish remover with a proprietary blend of solvents, waxes and thickening agents. These waxes seal in the solvent after being applied and allow the product to stay wet for an extended period of time; making it possible to remove multiple coats of paint or varnish with only one application.



850 STRIP THIS!™ can be brushed, trowelled or sprayed on. When brushing, lay on an even coat of stripper on the surface. **DO NOT BRUSH OUT.** When trowelling lay an even 1/16th over entire surface. When spraying, spray an even coat of approximately 1/16th over entire surface. On all 3 applications you must allow the product to perform before you break the surface of the stripper to start your clean up. A typical strip time for most coatings is between 2 to 4 hours on average. Leaving **850 STRIP THIS!™** to work longer will result in much less scraping and cleaning. Let the stripper do the work for you. If any residue is still on the stripped surface, scrub with a nylon Scotch Brite pad and additional **855 STRIP THIS!™ LIQUID** to remove the balance of residue. It is also ideal for cleaning spray equipment, lines, hoses, brushes and rollers.