



810
COLOR PATH™
By Imco®

"READY TO USE"

"NO PRIMER REQUIRED"

DESCRIPTION

COLOR PATH™ is a special blend of high bonding acrylics and synthetic, UV resistant pigments designed to protect asphalt, concrete, metal and wood from deterioration and beautify in vibrant colors.

The transformation is immediate and inexpensive. **COLOR PATH™** provides a decorative, skid resistant surface. **COLOR PATH™** has a memory to expand and contract back to original form. **COLOR PATH™** will bridge most small cracks in surface.

USES

COLOR PATH™ is a multiple use product for wood, metal, concrete and asphalt. **COLOR PATH™** is used for driveways, pool decks, walkways, bike paths, golf car paths, ramps, industrial walkways, tennis courts, crosswalks and steps.

FEATURES

- **COLOR PATH™** has memory and is elastic
- Ready to use direct from the container
- Improved slip resistance
- Colored
- Can withstand extreme weather variations
- Extends life of base material
- Will not chip or peel
- Backed by Imco's® strict quality controls

SURFACE PREPARATION

Asphalt: Clean out all deteriorated areas and repair holes with Imco's® PAR 800 and cracks with a quality crack filler. Thoroughly clean surface with a high pressure water blast. Oil stains should be removed with a trisodium phosphate (TSP) and hot water with a scrub brush. Power wash entire area with clean water and let dry. Coat with **COLOR PATH™**

Concrete: Clean out cracks to a sound surface and repair with a good crack repair material. Thoroughly clean any oil stains with a trisodium phosphate (TSP) and hot water with a scrub brush. Power wash entire area and let dry. Coat with **COLOR PATH™**

Wood: Clean surface, end cuts must be primed with a good sealer prior to application of **COLOR PATH™**

Metal and Painted Surfaces: All painted surfaces must be sound and clean prior to coating **COLOR PATH™**. If any rust is present coat with Imco's® 510A ALUMINIZED PRIMER. Make sure paint is a flat finish and power washed before applying **COLOR PATH™**

IMCO TECHNOLOGIES
6254 SKYWAY RD., PO BOX 915
SMITHVILLE, ON. L0R 2A0

TEL 1-877-957-4626
FAX 905-527-0606

info@imcotecnologies.com
www.imcotecnologies.com

IMCO TECHNOLOGIES
3909 Witmer RD, Suite 1014
NIAGARA FALLS, NY 14305

810

COLOR PATH™

By Imco®

APPLICATION

Mix **COLOR PATH™** well before using. Use a drill and mixing paddle if possible. Apply **COLOR PATH™** to clean dry surface and squeegee, roll or brush to desired finish. Always apply in one direction to eliminate uneven finishes. 2nd coat must be applied in a right angled direction.

Application temperature range: 40°F - 90°F

COVERAGE

Coverage: 1st coat 90-100 square feet/US gallon
2nd coat 100-125 square feet/US gallon

CLEAN UP

Clean equipment with water.

LIMITATIONS

Avoid any area of standing water. **COLOR PATH™** may soften. Avoid any oil or high gloss finishes to surfaces being treated with **COLOR PATH™**. When applying, if product starts to ball or roll up dampen the surface. Do not store in direct sunlight. Do not apply in direct sunlight.

SAFETY

Please refer to SDS at www.imcotechnologies.com

WARRANTY DISCLAIMER

The information herein is to assist customers in determining whether our products are suitable for their application. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to the contents and suitability. We warrant that our products will meet our written specifications. Nothing herein shall constitute a warranty expressed or implied including any warranty of merchantability of fitness, nor is protection from any loss or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.

IMCO TECHNOLOGIES
6254 SKYWAY RD., PO BOX 915
SMITHVILLE, ON. L0R 2A0

TEL 1-877-957-4626
FAX 905-527-0606

info@imcotechnologies.com
www.imcotechnologies.com

IMCO TECHNOLOGIES
3909 Witmer RD, Suite 1014
NIAGARA FALLS, NY 14305