



# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY


TRADE NAME	JETSET 100 TRAFFIC COATING PART A		
PRODUCT USE	Odorless epoxy paint Colors: clear, white, black, grey, red, yellow		
MANUFACTURE'S NAME	IMCO TECHNOLOGIES 6254 SKYWAY RD., PO BOX 915 SMITHVILLE, ON. L0R 2A0	TEL 1-877-957-4626 FAX 905-527-0606	IMCO TECHNOLOGIES 3909 Witmer RD, Suite 1014 NIAGARA FALLS, NY 14305
EMERGENCY NUMBER	613-996-6666 or *666 CANUTEC 1-800-535-5053 UNITED STATES POISON INFORMATION CENTRE		

## 2. HAZARDS IDENTIFICATION



GHS07

CARCINOGENIC STATUS	Not considered carcinogenic by NTP, IARC, and OSHA.
TARGET ORGANS	Eye, skin.
HEALTH EFFECTS – EYE	Irritation to eyes.
HEALTH EFFECTS – SKIN	Irritation may occur. May cause skin sensitization in some individuals.
HEALTH EFFECTS – INGESTION	May cause drowsiness, dizziness, confusion or loss of coordination.
HEALTH EFFECTS – INHALATION	Irritates the respiratory passages, and inhalation of large quantities may be harmful.



NFPA



HMIS

5-MINIMAL; 4-SLIGHT; 3-MODERATE; 2-HIGH; 1-EXTREME

## 3.COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS NUMBER	WEIGHT %
Epoxy resin blend		100

## 4. FIRST AID MEASURES

FIRST AID – INHALATION	Move away from exposure and into fresh air. If symptoms persist seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet.
FIRST AID – SKIN	In case of contact with hot product, immediately flood the skin with large quantities of water. Remove contaminated clothing and shoes. If there is a burn, cover burn area with clean material and obtain medical attention.
FIRST AID – EYE	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention.
FIRST AID – INGESTION	If swallowed, Obtain medical attention immediately. Do not induce vomiting.

### INFORMATION FOR DOCTOR:

#### Most important symptoms and effects, both acute and delayed.

No further relevant information available.

#### Indications of any immediate medical attention and special treatment needed

No further relevant information available

## 5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.
SPECIAL HAZARDS DURING FIREFIGHTING	Material will not burn unless preheated. Clear area of all non—emergency personnel. Cool hot containers with water. Sufficient cooling with water should be achieved to prevent weakening of containers.
PROTECTIVE EQUIPMENT FOR FIRE FIGHTING	Wear full protective clothing when this material is present in the area of the fire. Determine need to evacuate. Use water spray to keep fire exposed containers cool.
EXPLOSION DATA – SENSITIVITY TO IMPACT	N/A
EXPLOSION DATA – SENSITIVITY TO STATIC DISCHARGE	N/A

## 6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES	Soak up spilled product with absorbent material such as clay, sand other suitable material. Place in a container and seal tightly for proper disposal. For large spills use vacuum trucks or pump to storage/salvage vessels. Any residue should be absorbed onto absorbent material as above.
PERSONAL PRECAUTIONS	Wear chemical goggles, body-covering protective clothing, chemical resistant gloves and rubber boots. Use a NIOSH-approved dust and mist respirator where spray mist occurs.
ENVIRONMENTAL PRECAUTIONS	Prevent the material from entering drains or watercourses. Notify authorities if spill has entered watercourse or sewer.

### REFERENCES TO OTHER SECTIONS

See Section 7 for information on safe handling  
 See Section 8 for information on personal protection equipment  
 See Section 13 for disposal information

## 7. HANDLING AND STORAGE

HANDLING	Avoid contact with eyes, skin and clothing. May cause skin sensitization. Wash with soap and water before eating, drinking applying cosmetics or using toilet facilities. Launder contaminated clothing before use. Leather articles cannot be decontaminated and should be discarded. Avoid breathing mist. Keep container closed. Promptly clean up spills.
STORAGE	Store in a cool, dry place with adequate ventilation. . Keep containers closed when not in use. Keep away from open flames and high temperatures.

### INFORMATION ABOUT PROTECTION AGAINST EXPLOSIONS AND FIRES:

Keep ignition sources away – Do NOT Smoke  
 Protect against electrostatic charges

### SPECIFIC END USE(S)

No further relevant information available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROL MEASURES	Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within direct access.
RESPIRATORY PROTECTION	No respiratory protection is required during normal conditions of use.
HAND PROTECTION	Chemical resistant gloves should be worn during all handling operations.
EYE PROTECTION	Chemical goggles should be worn, if there is potential of contact with eyes.
BODY PROTECTION	Discard contaminated protective equipment. If there is danger of splashing, wear overall or apron.
PROTECTION DURING APPLICATION	During application, adequate ventilation must be provided. Mix in a well-ventilated area. If ventilation is poor, wear respiratory protection. Dries to form glass film which can easily cut the skin. Spilled material is very slippery. Can etch glass if not promptly removed.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid
ODOUR & APPEARANCE	No odor, clear, white, black, grey, red, yellow as per label description.
ODOR THRESHOLD (ppm)	NA
SPECIFIC GRAVITY	1.1 -1.2
VAPOR DENSITY (AIR = 1)	ND

VAPOR PRESSURE 20 C	ND
EVAPORATION RATE	ND
BOILING POINT (°C)	>260°C/500°F
FREEZING POINT (°C)	ND
FLASH POINT	249°C/480°F
pH	NA
COEFFICIENT OF WATER/OIL DISTRIBUTION	ND
SOLUBILITY IN WATER	Immiscible
VOC (g/l)	0
FLASH POINT (PMCC) (°C/F)	
UPPER FLAMMABLE LIMIT %VOL	NA
LOWER FLAMMABLE LIMIT %VOL	NA
AUTOIGNITION TEMP (°C/F)	NA

## 10. STABILITY AND REACTIVITY

STABILITY	Stable under normal conditions
CONDITIONS TO AVOID	Avoid high temperatures.
MATERIALS TO AVOID	Can react vigorously with strong oxidizing agents, strong levels of mineral acid, and strong mineral and organic bases. Do not allow hot material to contact water or other liquids. This can cause violent eruptions, splutter hot material or ignite flammable liquid.
HAZARDOUS POLYMERIZATION	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS	Aldehydes, carbon monoxide and carbon dioxide.

## 11. TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE	Low toxicity.
EFFECTS OF CHRONIC EXPOSURE	May cause irritation and sensitization on repeated contact.
EXPOSURE LIMITS	ND
IRRITANCY	Moderate irritation
SENSITIZATION	May cause sensitization on repeated exposure.
CARCINOGENICITY	Not listed as a carcinogen by IARC, NTP or OSHA. Carcinogen tests negative on major component.
REPRODUCTIVE TOXICITY	ND
TERATOGENICITY	ND
MUTAGENICITY	No evidence of mutagenicity of major component
TOXICOLOGICALLY SYNERGISTIC PRODUCTS	ND

## 12. ECOLOGICAL INFORMATION

MOBILITY	Complete information not available
PERSISTENCE/DEGRADABILITY	Complete information not available
BIO-ACCUMULATION	Complete information not available
ECOTOXICITY	Complete information not available

### RESULTS of PBT and vPvB Assessment

PBT: N/A  
vPvB: N/A

## 13. DISPOSAL CONSIDERATIONS

PRODUCT DISPOSAL	Absorb product on an inert material (sand or earth) and transfer absorbed product into a waste container. Dispose of in accordance with all applicable local and national regulations.
CONTAINER DISPOSAL	Labels should not be removed from containers until they have been cleaned. Empty containers may contain hazardous residues. Dispose of containers with care.

### UNCLEANED PACKAGINGS

**Recommendation:** Disposal must be made according to official regulations

**14. TRANSPORTATION INFORMATION**

CANADA		TDG CLASSIFICATION
HAZARD LABEL	NOT REQUIRED	NOT REGULATED
MARINE POLLUTANT		NO
SPECIFIC PRECAUTIONS FOR USER		N/A

**15. REGULATORY INFORMATION**

WHMIS CLASSIFICATION: CLASS D, DIV.2, SUBDIVISION B-Material causing other toxic effects.
CEPA STATUS (DSL) : All of the ingredients of this product are listed on the Domestic Substances List.
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by CPR.
DOT Description: combustible liquid n.o.s.
Hazard Class: C
Hazard Label: None
Packing Group: III (only if over 119 gallons or 450 litres)

**16. OTHER INFORMATION**

HAZARD RATING NFPA	HEALTH: 4      FLAMMABILITY: 3      REACTIVITY: 5 5-MINIMAL; 4-SLIGHT; 3-MODERATE; 2-HIGH; 1-EXTREME
KEY	NA: No applicable information found or available CAS#: Chemical Abstracts Service Number ACGIH: American Conference of Governmental Industrial Hygienists OSHA: Occupational Safety and Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit STEL: Short Term Exposure Limit NTP: National Toxicology Program IARC: International Agency for Research on Cancer R: Risk S: Safety LD50: Lethal Dose 50% LC50: Lethal Concentration 50%
PREPARED BY:	IMCO Technologies Inc.

SDS REVISION DATE	November 8, 2018
-------------------	------------------

Provided data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, however, each user should review these recommendations.